



**ALSEY**  
refractories co.

# SAFETY DATASHEET

## EXETER 90P

### 1 IDENTIFICATION

PROUCT NAME:	EXETER 90P	EMERGENCY CONTACT:
CHEMICAL NAME:	90% ALUMINA REFRACTORY BRICK	1-314-963-7900
PRODUCT USE:	HIGH TEMPERATURE INDUSTRIAL APPLICATIONS	MONDAY THRU THURSDAY, 09:00 – 15:00 US CENTRAL TIME [UTC-5]
MANUFACTURER:	ALSEY REFRACTORIES COMPANY 266 STATE ROUTE 106 SOUTH ALSEY, IL 62610 1-314-963-7900	

### 2 HAZARD IDENTIFICATION

HAZARD CLASSIFICATION: SPECIFIC TARGET ORGAN TOXICITY, REPEATED EXPOSURE – CATEGORY 1  
 CARCINOGENICTY – NONE  
 SERIOUS SKIN CORROSION/IRRITATION – CATEGORY 2  
 EYE DAMAGE/EYE IRRITATION – CATEGORY 3  
 SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE – NONE

SIGNAL WORD: **DANGER**

HAZARD STATEMENTS: INHALATION  
 CAUSES MILD SKIN IRRITATION  
 CAUSES EYE IRRITATION

PICTOGRAM:



PRECAUTIONARY STATEMENTS:

PREVENTION: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED. WASH THOROUGHLY AFTER HANDLING.

RESPONSE:

EYE IRRITATION: REMOVE CONTACT LENSES AND RINSE EYES SEEK MEDICAL ATTENTION IF NECESSARY

SKIN IRRITATION: WASH WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF NECESSARY

BREATHING: IF DIFFICULTY BREATHING REMOVE TO FRESH AIR, KEEP AT REST SEEK IMMEDIATE MEDICAL ATTENTION.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS-NO	WEIGHT %
ALUMINOSIICATE	1302-93-8	1-10
ALUMINUM OXIDE	1344-28-1	80-95

### 4 FIRST AID MEASURES

**INHALATION:** FIRST AID NOT GENERALLY REQUIRED. IF DIFFUCLTY BREATHING OCCURS WHILE BREATHING DUST, MOVE THE PERSON TO FRESH AIR AND SEEK MEDICAL ATTENTION ONLY IF NECESSARY.

**SKIN CONTACT:** IF SKIN IRRITATION OCCURS, WASH THOUROUGHLY WITH SOAP AND WATER.

**EYE CONTACT:** WASH IMMEDIATELY WITH WATER. DO NOT RUB EYES. REMOVE CONTACT LENSES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS

**ACUTE/DELAYED:** EYES – PARTICULATES MAY CAUSE ABRASIVE EYE DAMAGE  
INHALATION – MAY CAUSE RESPIRARTORY TRACT IRRITATION

ROUTES OF ENTRY: EYES, SKIN, INHALATION

### 5 FIRE FIGHTING MEASURES

NON-FLAMMABLE, NON-COMUBSTABLE, NON AUTO-IGNITING

NO SPECIAL INSTRUCTIONS OR CONDITIONS EXIST

### 6 ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS:** PRODUCT IS NOT A SPILL NOR AN ENVIORNMENTAL HAZARD.

**SMALL/LARGE SPILL:** FOR BROKEN SHAPES/FRAGMENTS; SWEEP, SHOVEL OR PICK UP AND PLACE IN CONTAINER FOR DISPOAL.

**METHODS FOR CLEAN UP:** DISPOSE CONTAMINATED MATERIAL AS WASTE ACCORDING TO SECTION 13. ENSURE ADEQUATE VENTILATION.

### 7 HANDLING AND STORAGE

**HANDLING:** PREVENT FORMATION OF DUST. ENSURE PROPER VENTILATION. KEEP RESPIRATORY DEVICE AVAILABLE.

**STORAGE:** STORE IN A DRY PLACE AWAY FROM EXTREME HEAT; MINIMIZE SKIN CONTACT.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

CHEMICAL NAME	CAS-NO	OSHA PEL (RESPIRABLE DUST)
ALUMINOSILICATE	1302-93-8	5 mg/m <sup>3</sup>

ENGINEERING GENERAL MECHANICAL VENTILATION IS USUALLY ADEQUATE.

MEASURES: EYE/FACE GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS SHOULD BE WORN.

SKIN AND BODY PROTECTION: IMPERVIOUS GLOVES AND LONG-SLEEVED AND LONG-LEGGED CLOTHING SHOULD BE WORN TO PREVENT SKIN CONTACT. SAFETY SHOES SHOULD BE WORN TO PREVENT FOOT INJURY FROM ACCIDENTALLY DROPPED BRICKS.

RESPIRATORY PROTECTION: USE A NIOSH APPROVED RESPIRATOR WHEN WORKING AROUND MATERIAL AND WHEN REMOVING THIS PRODUCT AFTER SERVICE. A RESPIRATORY PROTECTION PROGRAM SHOULD BE IMPLEMENTED IF EXPOSURES EXCEED OSHA PELs.

WORK/HYGIENIC PRACTICES: AVOID CONTACT WITH SKIN, EYES AND CLOTHING. AFTER HANDLING THIS PRODUCT, WASH HANDS BEFORE EATING OR DRINKING.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE:	CREAM TO WHITE/VARIOUS	AUTO IGNITION:	PRODUCT IS NOT SELF-IGNITING
PHYSICAL STATE:	SOLID	ODOR:	NONE
PH:	NOT APPLICABLE	WATER SOLUBILITY:	INSOLUBLE
FLASH POINT:	NOT APPLICABLE	EXPLOSION LIMITS:	NOT AN EXPLOSION HAZARD
BOILING POINT:	NOT APPLICABLE	MELTING POINT:	>3400°F
SPECIFIC GRAVITY:	2.5-3.7 g/cc	BULK DENSITY (G/CC):	2.92

**10 STABILITY AND REACTIVITY**

STABILITY: INCOMPATIBLE PRODUCT IS STABLE UNDER NORMAL CONDITIONS OF USE, STORAGE, AND TRANSPORTATION.

PRODUCTS: CONDITIONS PRODUCT CAN REACT WITH CONCENTRATED ACIDS.

TO AVOID: AVOID DUST FORMATION.

**11 TOXICOLOGICAL INFORMATION**

ACUTE TOXICITY-- PRODUCT INFORMATION: NO DATA FOR LD50 OR LC50 FOR ORAL, DERMAL OR INHALATION ROUTES OF ADMINISTRATION.

CHRONIC TOXICITY: IRRITANT TO SKIN AND MUCOUS MEMBRANES.

CARCINOGENICITY: NONE KNOWN.

TARGET ORGAN EFFECTS: LUNGS, EYES, RESPIRATORY SYSTEM, SKIN

**12 ECOLOGICAL INFORMATION**

ECO TOXICOLOGICAL/CHEMICAL FATE INFORMATION: NOT AVAILABLE.

### 13 DISPOSAL INFORMATION

DISPOSAL OF PRODUCT: AS SUPPLIED, PRODUCT MAY BE DISPOSED OF IN AN APPROVED LANDFILL, IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

PACKAGING DISPOSAL: REUSE, RECYCLE OR TREAT AS INDUSTRIAL WASTE.

### 14 TRANSPORT INFORMATION

U.S.A. DOT: NOT REGULATED.

CANADIAN TDG: NOT REGULATED.

ADDITIONAL INFORMATION: NOT DANGEROUS ACCORDING TO AVAILABLE INFORMATION.

### 15 REGULATORY INFORMATION

#### INTERNATIONAL INVENTORIES

TSCA: THIS SUBSTANCE OR ALL THE INGREDIENTS OF THIS PRODUCT ARE ON THE CHEMICAL SUBSTANCES INVENTORY OF THE TOXIC SUBSTANCES CONTROL ACT (TSCA INVENTORY). THE PRESENCE ON THIS LIST DOES NOT REQUIRE ANY LEGAL REPORTING. ALL COMPONENTS LISTED.

DSL: ALL COMPONENTS LISTED.

#### U.S. FEDERAL REGULATIONS

SARA 313: NO MATERIAL LISTED IN THE COMPONENTS IN SECTION 3 OF THIS MSDS IS ON THE SARA 313 LIST.

CALIFORNIA: CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS CRYSTALLINE SILICA, CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

OTHER STATES: CRYSTALLINE SILICA PRODUCTS ARE NOT KNOWN TO BE REGULATED BY STATES OTHER THAN CALIFORNIA; HOWEVER, STATE AND LOCAL OSHA AND EPA REGULATIONS MAY APPLY TO THESE PRODUCTS. CONTACT YOUR LOCAL AGENCY IF IN DOUBT.

#### WHMIS HAZARD CLASS

NOT CONTROLLED.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

### 16 OTHER INFORMATION

#### **REMOVAL OF REFRACTORIES:**

DUE TO THE PRESENCE OF DUST, CAUTION SHOULD BE USED DURING TEAR-OUT.

- 1 EMPLOYEES SHOULD BE APPRISED OF THE HAZARDS AND PRECAUTIONS FOR SAFE USE AND/OR EXPOSURE.
- 2 DUST GENERATION SHOULD BE MINIMIZED BY THE USE OF DUST CONTROL EQUIPMENT OR WATER SPRAY.
- 3 WEAR PROTECTIVE CLOTHING AND VACUUM CLEAN PRIOR TO REMOVING CLOTHING.

NOTE: THIS SAFETY DATA SHEET CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION AND IS NOT TO BE DISCLOSED TO THE GENERAL PUBLIC OR TO COMPETITION EXCEPT AS REQUIRED BY LAW. THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH ALSEY REFRACTORIES COMPANY OR NOT. THIS INFORMATION IS OFFERED SOLELY FOR USE IN YOUR EVALUATION OF THIS PRODUCT IN RESPECT TO SAFETY, HEALTH, AND ENVIRONMENTAL HAZARDS.

**SDS STATUS: REPLACES ALL PRIOR SDS  
SDS END**